

## 60 M BAND EMISSION REQUIREMENTS

Emission type	Emission designator	Restricted to:
Phone .....	2K80J3E .....	Upper sideband transmissions (USB).
Data .....	2K80J2D .....	USB (for example, PACTOR-III).
RTTY .....	60H0J2B .....	USB (for example, PSK31).
CW .....	150HA1A .....	Morse telegraphy by means of on-off keying.

(ii) The following requirements also apply:

(A) When transmitting the phone, RTTY, and data emissions, the suppressed carrier frequency may be set as specified in § 97.303(h).

(B) The control operator of a station transmitting data or RTTY emissions must exercise care to limit the length of transmission so as to avoid causing harmful interference to United States Government stations.

[54 FR 25857, June 20, 1989; 54 FR 30823, July 24, 1989, as amended at 54 FR 39537, Sept. 27, 1989; 60 FR 15688, Mar. 27, 1995; 65 FR 6550, Feb. 10, 2000; 69 FR 24997, May 5, 2004; 77 FR 5412, Feb. 3, 2012; 79 FR 35291, June 20, 2014]

#### § 97.309 RTTY and data emission codes.

(a) Where authorized by §§ 97.305(c) and 97.307(f) of the part, an amateur station may transmit a RTTY or data emission using the following specified digital codes:

(1) The 5-unit, start-stop, International Telegraph Alphabet No. 2, code defined in ITU-T Recommendation F.1, Division C (commonly known as “Baudot”).

(2) The 7-unit code specified in ITU-R Recommendations M.476-5 and M.625-3 (commonly known as “AMTOR”).

(3) The 7-unit, International Alphabet No. 5, code defined in IT-T Recommendation T.50 (commonly known as “ASCII”).

(4) An amateur station transmitting a RTTY or data emission using a digital code specified in this paragraph may use any technique whose technical characteristics have been documented publicly, such as CLOVER, G-TOR, or Pactor, for the purpose of facilitating communications.

(b) Where authorized by §§ 97.305(c) and 97.307(f), a station may transmit a RTTY or data emission using an unspecified digital code, except to a station in a country with which the

United States does not have an agreement permitting the code to be used. RTTY and data emissions using unspecified digital codes must not be transmitted for the purpose of obscuring the meaning of any communication. When deemed necessary by a Regional Director to assure compliance with the FCC Rules, a station must:

(1) Cease the transmission using the unspecified digital code;

(2) Restrict transmissions of any digital code to the extent instructed;

(3) Maintain a record, convertible to the original information, of all digital communications transmitted.

[54 FR 25857, June 20, 1989, as amended at 54 FR 39537, Sept. 27, 1989; 56 FR 56172, Nov. 1, 1991; 60 FR 55486, Nov. 1, 1995; 71 FR 25982, May 3, 2006; 71 FR 66465, Nov. 15, 2006; 80 FR 53753, Sept. 8, 2015]

#### § 97.311 SS emission types.

(a) SS emission transmissions by an amateur station are authorized only for communications between points within areas where the amateur service is regulated by the FCC and between an area where the amateur service is regulated by the FCC and an amateur station in another country that permits such communications. SS emission transmissions must not be used for the purpose of obscuring the meaning of any communication.

(b) A station transmitting SS emissions must not cause harmful interference to stations employing other authorized emissions, and must accept all interference caused by stations employing other authorized emissions.

(c) When deemed necessary by a Regional Director to assure compliance with this part, a station licensee must:

(1) Cease SS emission transmissions;

(2) Restrict SS emission transmissions to the extent instructed; and

(3) Maintain a record, convertible to the original information (voice, text,